AD-A261 446

1

**NSWC TR 90-284** 

# NOTES ON THE APPLICATION OF APPARENT MASS EFFECTS ON PARACHUTE DEPLOYMENT

BY W. P. LUDTKE

**UNDERWATER SYSTEMS DEPARTMENT** 

28 MAY 1990

S DTIC ELECTE D MAR 0 5 1993

Approved for public release; distribution is unlimited.

93-04739




# **NAVAL SURFACE WARFARE CENTER**

Dakigran, Virginia 22446-5000 o Silver Spring, Maryland 20063-5000

# NOTES ON THE APPLICATION OF APPARENT MASS EFFECTS ON PARACHUTE DEPLOYMENT

# BY W. P. LUDTKE UNDERWATER SYSTEMS DEPARTMENT

28 MAY 1990



TO THE PART OF THE

Approved for Public Release; distribution is unlimited.



Dahlgren, Virginia 22448-5000 • Silver Spring, Maryland 20903-5000

#### FOREWORD

The role of apparent mass effects in determining the magnitude of parachute opening shock force have been studied for many years. The ideas proposed in this report present arguments that the apparent mass effects may be neglected in calculating parachute opening shock force when using the dynamic drag area method of solution. It is also argued that the partial collapse of round personnel parachutes, at full inflation, may be due to the inertia of the entrapped air mass in concert with an air mass from aft of the canopy.

Approved by:

C. A. KALIVRETENOS, Deputy Underwater Systems Department

#### ABSTRACT

This report sets forth, without experimental proof, the reasons as to why the author feels that apparent mass effects in parachute deployment are not as important to the analysis derived in Reference (1) as usually perceived. This commentary applies to the parachute opening shock phase of deployment. Canopy-wake recontact which occurs after the canopy has been fully inflated for a definite period of time is a different problem. In the final phase of finite mass deployments the unrestrained air mass that inflated the canopy has a higher trajectory velocity than the parachute system. This higher trajectory velocity together with changes in the canopy shape catapults the air mass from the parachute resulting in a temporary loss of system mass which tends to compensate for other air masses that may have been added. Infinite mass deployments also have added air masses in addition to the air mass contained within the canopy. Dynamic drag areas obtained from infinite mass deployments implicitly include these effects. In infinite mass deployments where the velocity differential between the internal air mass and the system are minimal the deflation effects will not occur. The validity of these ideas can be verified by the comparison between calculated and experimental results.

#### CONTENTS

																							Page
INTRODUCTION	•		•			•	•	•			•	٠	•		•	•		•				•	1
APPROACH	•	•		•			•	•				•	•					•		•			1
THE TRANSIT	ïIC	NO.	01	· 1		E 1		FL#	AT]	INC	G (	CAN		Y.		•			•			•	1
SYSTEM VELO	C	ĮΤ	7 1	PRO	FI	LLE	E I	UI	RII	NG	II	1FI	LA?	ric	NC								6
EXAMPLE 1																							
CONCLUSIONS.			•			•		•		•					•				•	•			11
REFERENCES .					•						•	•	•	•			•	٠				•	12
NOMENCLATURE											•	•	•		•	٠		•					13
DISTRIBUTION																		٠					(1)

#### ILLUSTRATIONS

Figure		Pa	age
1	DYNAMIC DRAG-AREA RATIO VERSUS DIMENSIONLESS FILLING TIME		3
2	SOLID CLOTH PARACHUTE GEOMETRY AT SUSPENSION LINE STRETCH AND AT THE TIME to	•	4
3	VARIATION OF THE INFLATION REFERENCE TIME AS A FUNCTION OF SYSTEM WEIGHT FOR THE FLAT CIRCULAR SOLID CLOTH PARACHUTE OF EXAMPLE 1	•	8
4	TRAJECTORY VELOCITY PROFILE OF THE INFLATING SOLID CLOTH PARACHUTE OF EXAMPLE 1	•	10

#### INTRODUCTION

The dynamic drag area signatures of Figure 1 were obtained from infinite mass wind tunnel deployments of the several model parachutes. The application of the infinite mass dynamic drag area signatures to finite mass deployments has raised some questions, by other experimenters, in concern for apparent mass effects. The thoughts expressed in this report present why I feel that parachute apparent mass related to parachute opening shock force is not as strong an effect as usually believed. Opening shock effects are not the same problem as wake reattachment after full canopy inflation. Apparent mass may also be important in parachute stability. Recent conversations with other experimenters as to apparent mass effects indicates that they are asking similar questions. Therefore, these ideas are offered even though they have not been experimentally substantiated.

Observation of inflating personnel parachutes often shows that the canopy fully inflates and then attempts to turn inside out as the crown of the canopy moves forward and approaches the plane of the skirt hem. This deflation is attributed to the apparent mass pushing on the canopy from behind. If this is true then apparent mass effects should be significant. However, there are other events, indistinguishable by the naked eye, taking place at the same time which would produce the identical result and reduce the magnitude of the apparent mass effects. Two main events occur during the inflation cycle of the parachute that affect the added air mass performance.

#### **APPROACH**

The first event is the change in the canopy shape as the included air mass is collected, and the second is the velocity and kinetic energy of the included air mass and its relationship to the system velocity.

THE TRANSITION OF THE INFLATING CANOPY GEOMETRY

Figure 2 depicts the transition of the geometry of a solid cloth parachute from the stretched out geometry at line stretch to the inflated geometry at the time t. As air mass is collected the developing suspension line cone angle causes the canopy skirt hem to accelerate forward toward the payload. At the same time




FIGURE 1. DYNAMIC DRAG-AREA RATIO VERSUS DIMENSIONLESS FILLING TIME




FIGURE 2. SOLID CLOTH PARACHUTE GEOMETRY AT SUSPENSION LINE STRETCH AND AT THE TIME  $\mathfrak{t}_{\mathbf{0}}$ 

the canopy vent and the entrapped air mass has an additional forward acceleration applied. With reference to Figure 1, the solid cloth parachutes develop drag area slowly at first and then more rapidly as the canopy inflates. The drag area growth represents a growth of the canopy radially; that is perpendicular to the trajectory. This radial growth accelerates as the canopy inflates. The acceleration is represented by the instantaneous slope of the dynamic drag area signatures in Figure 1. As the radial growth accelerates the parachute vent and crown area should be under severe accelerations along the trajectory in order to keep pace with the radial inflation. Acceleration of the canopy cloth also accelerates the air mass contained within the canopy and raises the velocity and kinetic energy level of the entrapped air.

#### SYSTEM VELOCITY PROFILE DURING INFLATION

The next consideration is the system velocity profile during inflation. Finite mass deployments exhibit substantial trajectory velocity reduction during canopy inflation. As weight is added to the system the velocity profile has less variation, the canopy inflates faster, the opening shock force increases and occurs later in the inflation process. Example 1 illustrates how the velocity profile varies during inflation of a solid cloth parachute for finite mass thru infinite mass weight-to-drag-area ratios.

Example 1: Determine the velocity profile during canopy inflation of a 200 lb. payload being recovered by a 30 gore solid cloth parachute with a D = 35 ft. when deployed at 1000 ft altitude with the following system parameters. Vary W/CpS to illustrate finite thru infinite mass performance.

Let  $\rho$  = 0.002309 slugs/FT<sup>3</sup>, k=1.46, C<sub>p</sub>=1.7, A<sub>so</sub>=962.1 FT<sup>2</sup>, A<sub>MO</sub>=399.53 FT<sup>2</sup>,  $\underline{V}_{O}$  = 4690.83 FT<sup>3</sup>,  $\underline{V}_{S}$ =250 FPS.

1. Inflation distance,  $V_st_o$ , from Reference 1.

$$V_{S}t_{O} = \frac{14W}{\rho gC_{D}S_{O}} \begin{bmatrix} \frac{g \rho Y_{O}}{2W} \left[ \frac{C_{D}S_{O}}{A_{MO} - A_{SO} k \left( \frac{C_{\rho} \rho}{2} \right)^{\frac{1}{2}}} \right] \\ -1 \end{bmatrix} \qquad (1)$$

for the given problem data

 $V_{st_0} = 284.56 \text{ FT}$ 

2. Inflation reference time,  $t_0$ .

$$t_{0} = \frac{V_{s}t_{0}}{V_{s}}$$

$$t_{0} = \frac{284.56}{250}$$

$$t_{0} = 1.138 \text{ SEC}$$
(2)

3. Empirical inflation time,  $t_f$ .

$$t_0 = t_f = \frac{nD_0}{V_s}$$

$$t_0 = t_f = \frac{8 \times 35}{250}$$

$$t_0 = t_f = 1.120 \text{ SEC}$$
(3)

The two independent methods of calculating the parachute inflation time show a reasonable agreement. The advantage of Equation (1) is the ability to adjust the inflation time for variation of the several parameters. In this example, weight. See Figure 3 for the effects of  $\text{W/C}_{\text{D}}\text{S}_{\text{O}}$  on the inflation time.


4. Ballistic Mass Ratio

$$M = \frac{2W}{\rho g V_s t_0 C_D S_0}$$

$$M = \frac{2 \times 200}{0.002309 \times 32.2 \times 250 \times 1.138 \times 721}$$

$$M = 0.0262$$
(4)

M = 0.0262 which is below the limiting value of  $M_L$  = 0.1907 for finite mass operation



VARIATION OF THE INFLATION REFERENCE TIME AS A FUNCTION OF SYSTEM WEIGHT FOR THE FLAT CIRCULAR SOLID CLOTH PARACHUTE OF EXAMPLE 1 FIGURE 3.

w.c<sub>0</sub>s<sub>0</sub> шв гт<sup>2</sup>;

#### 5. Velocity equation

$$\frac{V}{V_S} = \frac{1}{1 + \frac{1}{7M} \left(\frac{t}{t_o}\right)^7} ; \tau = 0$$
 from Table 1, Reference 1 (5)

$$V = \frac{250}{1 + 5.453 \left(\frac{t}{t_0}\right)^7}$$

The velocity-time ratio results are plotted in Figure 4 for several weight-to-drag-area ratios which result in performance modes of finite mass through infinite mass. In the finite mass deployment mode half of the inflation time is required to lower the trajectory velocity by 10 fps as compared to the last half of the inflation cycle where the trajectory velocity is reduced an additional 200 fps. During this final deceleration the higher velocity and kinetic energy of the entrapped air mass, including the vent and skirt hem acceleration effects, propel the entrapped air from the canopy mouth as though it were in a catapult. As the air leaves the canopy the crown cloth follows as if it were only being pushed from behind by the external apparent mass. As the mode of operation approaches infinite mass the velocity reduction during inflation approaches zero and the differential velocity between the system and the entrapped air mass is minimized. Deployments where there is minimal velocity differential between the entrapped air mass and the system do not exhibit catastrophic deflation as do finite mass deployments where the entrapped masssystem velocity differential at t/t =1 is substantial.




FIGURE 4. TRAJECTORY VELOCITY PROFILE OF THE INFLATING SOLID CLOTH PARACHUTE OF EXAMPLE 1.

Parachutes are designed to be flexible structures. This flexibility and the subsequent partial collapse at full inflation give the appearance of a substantial air mass overtaking the parachute from behind. If, however, the canopy motion is due to the catapulting of the entrapped air mass the actual "other" associated air mass may be small enough to be neglected in the analysis. A rigid, no airflow, parachute shape may perform quite differently and have a much larger apparent mass. What is needed is a "seat belt" to restrain the included air within canopy.

#### CONCLUSIONS

- 1. As a result of the canopy accelerations and the catapult effect, the actual apparent mass effects due to air striking the canopy from behind may be much less than expected. If this is so the use of drag area signatures obtained from infinite mass deployments should be applicable to the finite mass case.
- 2. In infinite mass deployments the canopy geometry transitions as in finite mass deployments but the inflation time is reduced. Since the trajectory velocity of the parachute system and the entrapped air remain the same, the catapult effect is minimal. Any effects that may be in the system due to canopy accelerations are not visible to the observer.
- 3. The inertial effects of the air mass within the inflating canopy must be taken into account when addressing parachute apparent mass.
- 4. Parachute canopy flexibility is a factor in reducing apparent mass effects.
- 5. The difficulty in finding a solution to a given problem and the input required to accomplish the solution are directly related to the approach to the problem.

#### REFERENCES

- 1. William P. Ludtke, NOTES ON A GENERIC PARACHUTE OPENING FORCE ANALYSIS, NSWC TR 86-142, 1 March 1986
- 2. William P. Ludtke, OBSERVATIONS ON THE INFLATION TIME AND INFLATION DISTANCE OF PARACHUTES, NSWC TR 88-292, 28 May 1988

#### NOMENCLATURE

A <sub>MO</sub>	_	Steady-state inflated mouth area, FT <sup>2</sup>
So=Aso	-	Canopy surface area, FT <sup>2</sup>
c <sub>D</sub> s	-	Canopy drag area at any instant during inflation, FT
$c_{\mathtt{D}}^{s}$	-	Canopy drag area at the time $t=0$ , $FT^2$
$c_{D}s_{O}$	-	Canopy steady state drag area, FT <sup>2</sup>
c <sub>p</sub>	-	Average pressure coefficient is equal to the parachute drag coefficient based on projected area of the canopy.
D <sub>O</sub>	-	Nominal diameter of the aerodynamic decelerator = $\sqrt{4S_{\odot}/\pi}$ , FT
g	-	Gravitational acceleration, FT/SEC <sup>2</sup>
k	-	Canopy cloth permeability constant
М	-	Ballistic Mass Ratio - ratio of the mass of the retarded hardware (including parachute) to a mass of atmosphere contained in a right circular cylinder of length ( $v_{st_o}$ ), face area ( $v_{pt_o}$ ) and density ( $\rho$ )
$^{ m M}_{ m L}$	-	Limiting Ballistic Mass Ratio is the system mass ratio which causes the maximum opening shock to occur at t. The limiting BMR varies with the type of parachute
t	-	Instantaneous time, SEC
<sup>t</sup> f	-	Canopy inflation time when the inflated canopy has reached its maximum physical size, SEC
t <sub>o</sub>	-	Reference time when the parachute has reached the design drag area for the first time, SEC
v	-	Instantaneous system velocity, FT/SEC
$v_{o}$		System velocity at the time t=t <sub>o</sub> , FT/SEC

# NOMENCLATURE (cont)

v <sub>s</sub>	-	System velocity at the end of suspension line stretch, FT/SEC
Yo	-	Volume of air which must be collected during the inflation process, $\operatorname{FT}^3$
W	-	Hardware weight, including the parachute LB
W/C <sub>D</sub> S <sub>o</sub>	-	Ballistic coefficient, ratio of system weight to parachute steady state drag area, LB/FT
ρ	-	Air density, SLUGS/FT <sup>3</sup>
τ	-	Ratio of system drag to steady state drag area at t=0, ${\rm C_DS_i/C_DS_O}$

#### DISTRIBUTION

,	Copies	<u>Сорі</u>	<u>es</u>
ATTN LIBRARY	4	ATTN CODE 2027	2
AIR 931H		LIBRARY	
(F TERRY THOMASSON)	2	CODE 2029 (ONRL)	
TECHNOLOGY MANAGER		DIRECTOR	
CREW STATION & LIFE		NAVAL RESEARCH LABORATORY	
SUPPORT SYSTEMS		WASHINGTON DC 20375	
(JP#1-RM 424)		A (DVIDA' 1 11) 15 A 1837	• >
COMMANDER		ATTN LIBRARY	2
NAVAL AIR SYSTEMS COMMAND		U S NAVAL ACADEMY ANNAPOLIS MD 21402	
DEPARTMENT OF THE NAVY		ANNAPOLIS MID 21402	
WASHINGTON DC 20361		ATTN LIBRARY (CODE 0384)	2
A FEMALA ! A 19311 A 1831	4	SUPERINTENDENT	-
ATTN LIBRARY	4	US NAVAL POSTGRAĐUATE SCHOOL	
COMMANDER NAVALSEA SYSTEMS COMMAND		MONTEREY CA 93940	
WASHINGTON DC 20362		MONTAMATER 55540	
WASHINGTON DC 20302		ATTN LIBRARY	2
ATTN LIBRARY	2	DR NORMAN WARNER	1
NAVAL PERSONNEL RESEARCH	4	DR DONALD MCERLEAN	1
AND DEVELOPMENT CENTER		KENNETH GREENE	1
WASHINGTON DC 20007		WILLIAM B SHOPE	ì
WARITATION DE 2000		DAVID N DESIMONE	}
ATTN LIBRARY	4	LOUIS A DAULERIO	1
OFFICE OF NAVAL RESEARCH	-	TROMAS J POPP	ì
WASHINGTON DC 20360		MARIA C HURA	ì
		COMMANDING OFFICER	
ATTN FLUID DYNAMICS BRANCH	2	NAVAL AIR WARFARE CENTER	
STRUCTURAL MECHANICS		AIRCRAFT DIVISION WARMINSTER	
BRANCH	2	WARMINSTER PA 18974 2189	
OFFICE OF NAVAL RESEARCH			
800 N QUINCY ST		ATTN LIBRARY	2
ARLINGTON VA 22217		MARK T LITTLE	1
		COMMANDER	
ATTN LIBRARY	3	CRANE DIVISION	
CHRISTOPHER O'DONNELL		NAVAL SURFACE WARFARE CENTER	
(CODE 5920L	6	CRANE IN 47522 5000	
COMMANDER			
INDIAN HEAD DIVISION			
NAVAL SURFACE WARFARE CENTEI	}		
INTENDANGUERA IN MIN GOCAO 5000			

,	Copies	<u>C</u> e	<u>pies</u>
ATTN LIBRARY	2	ATTN TECHNICAL LIBRARY	2
ERIC SMITH	1	COMMANDING GENERAL	
COMMANDER		U S ARMY WEAPONS COMMAND	
NAVAL AIR WARFARE CENTER		RESEARCH AND DEVELOPMENT	
WEAPONS DIVISION		DIRECTORATE	
CHINA LAKE CA 93555 6001		ROCK ISLAND IL 61201	
ATTN LIBRARY	1	ATTN LIBRARY	2
COMMANDER		WALT KOENIG,	
CARDEROCK DIVISION		SMCAR-AET-A	1
NAVAL SURFACE WARFARE CENTER		ROY W KLINE,	
BETHESDA MD 20084 5000		SMCAR AET-A	1
		COMMANDING GENERAL	
ATTN TECHNICAL LIBRARY		U S ARMY ARDEC	
(CODE N0322)	2	DOVER NJ 07801	
COMMANDER			
NAVAL AIR WARFARE CENTER		ATTN TECHNICAL LIBRARY,	2
WEAPONS DIVISION		BLDG 313	
POINT MUGU CA 93042 5000		ARMING RESEARCH AND	
		DEVELOPMENT LABORATORIES"	
ATTN LIBRARY	2	ABERDEEN PROVING GROUND	
DIRECTOR		ABERDEEN MD 21005	
MARINE CORPS DEVELOPMENT AND	•	A (1)(1) A (1) A (1) A (1) A	
EDUCATION COMMAND		ATTN LIBRARY	2
DEVELOPMENT CENTER		COMMANDING GENERAL	121262
QUANTICO VA 22134		EDGEWOOD ARSENAL HEADQUART	ERS
ATA DIA PERMUANDAN TERRITORIA DA DA DA DA DESTADORA DE LA DEST		AERO RESEARCH GROUP	
MARINE CORPS LIAISON OFFICER		ABERDEEN PROVING GROUND	
U.S.ARMY NATICK LABORATORIES	o.	ABERDEEN MD 21005	
NATICK MA 01760	2	ATTN TECHNICAL LIBRARY	2
A TENNA TO DE COLONIA DE LO COMPANDO		COMMANDING GENERAL	<u>.</u>
ATTN TECHNICAL DOCUMENT CENTER	2	HARRY DIAMOND LABORATORIES	
"COMMANDING GENERAL	2	2800 POWDER MILL ROAD	
U S ARMY MOBILITY EQUIPMENT		ADELPHI MD 20783	
RESEARCH AND DEVELOPMENT		ADELL'III MID 20763	
CENTER		ATTN TECHNICAL LIBRARY	2
FT BELVOIR VA 22660		U S ARMY BALLISTIC RESEARCH	٠
1 1 DELY OIL VA 22000		LABORATORIES	
ATTN TECHNICAL LIBRARY	2	ABERDEEN PROVING GROUND	
STANLEY D KAHN	1	ABERDEEN MD 21005	
COMMANDING GENERAL			
U.S. ARMY MUNITIONS COMMAND			
DOVER NJ 07801			

•	Copies	<u>C</u>	<u>opies</u>
A BUDNE BUDGINAMO A LA LININA INV	0	N1000000000000000000000000000000000000	
ATTN TECHNICAL LIBRARY	2	PRESIDENT	4
COMMANDING GENERAL		U S ARMY AIRBORNE COMMUNICAT	1055
U S ARMY FOREIGN SCIENCE AND		AND ELECTRONIC BOARD	
TECHNOLOGY CENTER		FORT BRAGG NC 28307	2
220 SEVENTH STREET NE			
FEDERAL BUILDING		ATTN LIBRARY	2
CHARLOTTESVILLE VA 22312		COMMANDING GENERAL	
		U S MISSILE COMMAND	
ATTN LIBRARY	2	REDSTONE SCIENTIFIC INFORMATION	DN .
COMMANDING GENERAL		CENTER	
U S ARMY MATERIEL COMMAND WASHINGTON DC 20315		REDSTONE ARSENAL AL 35809	
		ATTN LIBRARY	2
ATTN LIBRARY	2	JAMES E. SADEK	1
COMMANDING GENERAL		PETER MASKE	1
U.S. ARMY TEST AND EVALUATION		CALVIN K LEE	I
COMMAND		M P GIONFRIDDO	1
ABERDEEN PROVING GROUND		JOSEPH GARDELLA	1
ABERDEEN MD 21005		TIMOTHY E. DOWLING	1
		JOHN CALLIGEROS	1
ATTN LIBRARY	2	CARL CALLIANNO	I
COMMANDING GENERAL		DRDNA-UAS	1
U.S. ARMY COMBAT DEVELOPMENTS		COMMANDER	
COMMAND		U S ARMY NATICK R&D LABS	
FT BELVOIR VA 22060		KANSIS STREET	
		NATICK MA 01760 5017	
ATTN TECHNICAL LIBRARY	2		
COMMANDING GENERAL		ATTN LIBRARY	2
U.S. ARMY COMBAT DEVELOPMENTS		COMMANDER	
COMMAND		U S ARMY AVIATION SYSTEMS	
CARLISLE BARRACKS, PA 17013		COMMAND	
		ST LOUIS MO 63166	
ATTN TECHNICAL LIBRARY	2		
COMMANDING GENERAL		ATTN LIBRARY	1
U.S. ARMY MATERIEL LABORATORIES	5	OFFICE OF THE CHIEF OF RESEARCI	i
FORT EUSTIS VA 23604		AND DEVELOPMENT	
		DEPARTMENT OF THE ARMY	
ATTN SYSTEMS AND EQUIPMENT		WASHINGTON DC 20315	
DIVISION	2		
U S ARMY AIR MOBILITY R&D		ATTN LIBRARY	1
LABORATORY		U S ARMY ADVANCED MATERIEL	•
EUSTIS DIRECTORATE		CONCEPTS AGENCY	
FORT EUSTIS VA 23604		DEPARTMENT OF THE ARMY	
		WASHINGTON DC 20315	

$\overline{\mathbf{c}}$	opies	Сор	<u>ics</u>
ATTN LIBRARY	2	ATTN LIBRARY	2
DIRECTOR		COMMANDING OFFICER	
U S ARMY MOBILITY R&D		AIR FORCE AEROPHYSICS	
AMES RESEARCH CENTER		LABORATORY	
MOFFETT FIELD CA 94035		HANSCOM FIELD MA	
ATTN LIBRARY	2	ATTN SA ALC/MMIR	2
NORMAN BRUNEAU	2	LIBRARY	2
COMMANDANT		COMMANDING OFFICER	
QUARTERMASTER SCHOOL		KELLY AFB TX 78241	
AIRBORNE DEPARTMENT			
FORT LEE VA 23801		ATTN LIBRARY/DOCUMENTS	2
		ARNOLD ENGINEERING	
ATTN RESEARCH/GENERAL MATERIA	١.	PEVELOPMENT CENTER (ARO INC)	
REPRESENTATIVE	2	ARNOLD AIR FORCE STATION	
U.S. ARMY STANDARDIZATION	_	TN 37389	
GROUPUK			
BOX 65		ATTN LIBRARY MAIL STOP 60-3	2
FPO NY 09510		NASA LEWIS RESEARCH CENTER	-
		21000 BROOKPARK ROAD	
ATTN LIBRARY	2	CLEVELAND OIL 44135	
COMMANDING OFFICER	~		
MCCALLAN AFB		ATTN LIBRARY CODE IS-CAS-42B	2
SA-ALC/MMIR		NASA JOHN F KENNEDY SPACE	
MCCALLAN AFB CA 95652		CENTER	
Moeth, Military City 50000		KENNEDY SPACE CENTER FL 32899	
ATTN WILLIAM CASEY ASD/ENECA	1	MINIMATE MED CINTING 17, 32,033	
WILLIAM PINNEL AFWAL/FIER	1	ATTN LIBRARY CODE BM6	
ROBERT HESTERS JR	•	NASA MANNED SPACECRAFT	
ASD/YYEE	1	CENTER	
E SCHULTZ AFWAL/FIER	i	2101 WEBSTER SEABROOK ROAD	
DANIELJ KOLEGA		HOUSTON TX 77058	
BLDG 25 AREA B	1	HOCSTON IN 11000	
HENGEL ASD/ENECA	1	ATTN LIBRARY	2
A KIDIDIS ASDÆNECA	1	GARY W JOHNSON	4
COMMANDING OFFICER	,	MAIL CODE PT21	1
WRIGHT-PATTERSON AFB		NASA MARSHALL SPACE FLIGHT	1
OH 45433			
On 49433		CENTER	
A'PPN(TIDDADA	0	HUNTSVILLE AL 25812	
ATTN LIBRARY	2		
COMMANDING OFFICER			
AIR FORCE SPACE DIVISION			
POBOX 92960			
WORLDWAY POSTAL CENTER LOS ANGELES CA. 90009			
TALES ASSOCIATED ASSOCIATION OF THE STATE OF			

	<u>Copies</u>		Copies
ATTN LIBRARY	2	ATTN LIBRARY MAIL 111-113	2
MENDLE SILBERT	1	JET PROPULSION LABORATORY	2
EARL B JACKSON	1	4800 OAK GROVE DRIVE	
DAVE MOLTEDO	1	PASEDENA CA 91103	
ANEL FLORES	1	PASSIMINA CA 91103	
PIHL EBERSPEAK	1	ATTN LIBRARY	2
NASA GODDARD SPACE FLIGHT	•	MAX ENGERT CODE EA	2
CENTER		JOE GAMBLE	2
WALLOPS ISLAND FLIGHT		MAIL CODE 1A143	2
FACILITY		KIRBY HINSON	2
WALLOPS ISLAND VA 23337		MAIL CODE ET13	2
WALLOUGISEALOU VA 20001		NASA JOHNSON SPACE CENTER	ڪ
ATTN LIBRARY	2	HOUSTON TX 77058	
NATIONAL AERONAUTICS AND	2	1100310N 1X 77000	
SPACE ADMINISTRATION		A SPENT THE CHARLE AT LEAD A D.V.	2
HEADQUARTERS MTG		ATTN TECHNICAL LIBRARY DEFENSE ADVANCED RESEARCH	4
400 MARYLAND AVENUE SW		PROJECTS AGENCY	
WASHINGTON DC 20546		1400 WILSON BOULEVARD	
WASHINGTON DC 20046			
ATTN RESEARCH PROGRAM		ARLINGTON VA 22209	
RECORDING UNIT		ATEUNT LIDDA DAZ ZERZOLINGO A LA	2
MAIL STOP 122	1	ATTN LIBRARY (TECHNICAL) DIRECTOR	4
RAYMOND L ZAVASKY	1	DEFENSE RESEARCH AND	
MAIL STOP 177	ì	ENGINEERING	
ANDREW S WRIGHT JR	'	THE PENTAGON	
MAIL STOP 401	8	WASHINGTON DC 20301	
GEORGE M WARR	0	WASHINGTON DC 20301	
NASA LANGLEY RESEARCH		MOROTO OF THE PROPERTY OF THE	,
CENTER		DIRECTOR OF DEFENSE RESEARCI	1
LANGLEY STATION		AND ENGINEERING	
		DEPARTMENT OF DEFENSE	13
HAMPTON VA 23365		WASHINGTON DC 20315	2
ATTN LIBRARY STOP 203-3	2	DEFENSE TECHNICAL INFORMATI	ON
JIM ROSS	1	CENTER	
NASA AMES RESEARCH CENTER		CAMERON STATION	
MOFFETT FIELD CA 94035		ALEXANDRIA VA 22314	12
ATTN LIBRARY	2	ATTN GIFT AND EXCHANGE	
NASA FLIGHT RESEARCH CENTER	4-	DIVISION	4
POBOX 273		LIBRARY OF CONGRESS	•
EDWARDS CA 93523		WASHINGTON DC 20540	
A //WEIN' T. HINTN A NAV	c	A COMPANY TO A MANAGE OF THE STATE OF THE ST	_
ATTN LIBRARY	2	ATTN DR W L GARRARD	2
NASA GODDARD SPACE FLIGHT		UNIVERSITY OF MINNESOTA	
CENTER		DEPARTMENT OF AEROSPACE	
GREENBELT MD 20771		ENGINEERING	
		MINNEAPOLIS MN 55455	

	Copies	Cor	pies
ATTN TECHNICAL REFERENCE		ATTN TECHNICAL INFORMATION	0
LIBRARY	2	CENTER	2
CENTER FOR NAVAL ANALYSES		ROCKWELLINTERNATIONAL	
4401 FORD ROAD ALEXANDRIA VA 32303-0268		CORPORATION	
ALEXANDRIA VA 32303-0268		SPACE AND INFORMATION	
ATTN CODE 1632	2	SYSTEMS DIVISION 12214 S LAKEWOOD BOULEVARD	
LIBRARY	2	DOWNEY CA 90241	
DR DEAN WOLF	1	DOWNET CA 90241	
DR CARL PETERSON	10	ATTN LIBRARY	2
R KURT BACA	10	PENNSYLVANIA STATE UNIVERSITY	۷
IRA T HOLT	1	APPLIED RESEARCH LABORATORY	
DONALD W JOHNSON	1	POBOX 30	
JAMES W PURVIS	1	STATE COLLEGE PA 16801	
HAROLD E WIDDOWS	1	STATE COLLEGE PA 10001	
JAMES STRICKLAND	1	ATTN R A RAUSCH (MN48-3700)	1
DON MCBRIDE	1	HONEYWELLINC	1
J MICHAEL MACHA	1	7225 NORTHLAND DRIVE	
SANDIA NATIONAL LABORATORIES	1	BROOKLYN PARK MN 55428	
ALBUQUERQUE NM 87185		DROOKLIN FARE MIN 99426	
ALBEQUERQUERM 67165		ATTN LIBRARY	2
ATTN DOCUMENT LIBRARIAN	2	NATIONAL BUREAU OF STANDARDS	2
APPLIED PHYSICS LABORATORY	Ĺ.	WASHINGTON DC 20234	
THE JOHNS HOPKINS UNIVERSITY		WASHINGTON DC 20234	
JOHNS HOPKINS ROAD		INTERNAL DISTRIBUTION	
LAUREL MD 20810		U (H D SMITH)	1
IMORIA MID 20010		U06 (J GOELLER)	1
ATTN LIBRARY	2	U13 (W PARSONS)	1
NATIONAL ACADEMY OF SCIENCES	۷	U13 (W P LUDTKE)	15
NATIONAL RESEARCH COUNCIL		U13 (D FISKE)	13
COMMITTEE ON UNDERSEA		U13 (J F MCNELJA)	}
WARFARE		U13 (J MURPHY)	1
2101 CONSTITUTION AVENUE NW		U13 (J CORRERLL)	i
WASHINGTON DC 20418		U 13 (S M HUNTER)	1
WASHINGTON INC 20416		U13 (R L PENSE)	1
ATTN TECHNICAL REFERENCE		U13 (M L LAMA)	1
LIBRARY	2	U43 (J ROSENBERG)	1
SANDIA CORPORATION	4.	E231	2
LIVERMORE LABORATORY		E232	3
P O BOX 969		E31 (GIDEP)	1
LIVERMORE CA 94550		C72W	i
WELLEN OF OTODO		01211	•
ATTN K FRENCH	1		
LOCKHEED MISSILES & SPACE CO			
POBOX 504			
SUNNYVALE CA 94086			

# REPORT DOCUMENTATION PAGE

Form Approved OMB No 0704 0188

Public reporting burden for this collection of information is distinated to average 3 hour per response, including the time for reviewing instrumicing search in \$44.5 mg mass su

gathering collection of Day's high	and maintaining the data needed, a of information, including suggestion way, Suite 1204, Arlington 124-1222	nd completing and reviewing the citlertic is for reducing this burden, to Arashingto 12-4302, and to the Office of Managemen	in of information - Send (timments in n Headquarters Services (Directorate t and Budget, Paperwork Requition)	egarding this builden estimate or an . Their evole flot this Mor information Operations and hebrits, 1215 yetters in Project (0704-0188). Washington, DC 20003
	NCY USE ONLY (Leave bia	nk) 2. REPORT DATE		AND DATES COVERED
		5/28/90	Final FY'8	7 to FY <b>'</b> 90
NOTES PARAC	CHUTE DEPLOYMENT	ION OF APPARENT MASS	S EFFECTS TO	S. FUNDING NUMBERS
6. AUTH	IOR(S)			
WILLI	AM P. LUDTKE			
7. PERFO	DRMING ORGANIZATION N	IAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION REPORT NUMBER
1090	al Surface Warfar Ol New Hampshire ver Spring, MD 2	Avenue		NSWC TR 90-284
9. SPON	SORING MONITORING AC	ENCY NAME(S) AND ADDRES	S(ES)	10. SPONSORING MONITORING AGENCY REPORT NUMBER
11. SUPP	PLEMENTARY NOTES			
12a. DIS	TRIBUTION AVAILABILITY	STATEMENT		12b. DISTRIBUTION CODE
Appro	ved for public re	elease; distribution	n is unlimited.	
autho to th appli which is a unres the p canop loss been air m mass where minim verif	r feels that apple analysis derives to the parachicoccurs after the different problem trained air mass arachute system. The system mass will added. Infinite mass contained will deployments implicate the deflation fied by the compa	arent mass effects in deference (1) at e opening shock plute opening shock plute canopy has been further inflated the canopy that inflated the canopy the air mass from the defends to compend mass deployments althin the canopy. Dyicitly include these afferential between the deferential between the deference of the canopy is a second to the canopy.	in parachute deployas usually percentase of deployment of the deployment of the parachute restant for other also have added airly namic drag areas a effects. In internal are recurs, The validities	
PARAC APPAR	HUTE TECHNOLOGY ENT MASS ULT EFFECT	FINITE MASS OF INTERMEDIATE PRINTER MASS	MASS OPERATION	15. NUMBER OF PAGES  16. PRICE CODE
	URITY CLASSIFICATION	18. SECURITY CLASSIFICATIO		IFICATION 20. LIMITATION OF ABSTRACT
OF	REPORT SSIFIFD	OF THIS PAGE	OF ABSTRACT	SAP